

THE COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, DC 20231

Docket: JA997028
PATENT

Sir:

Transmitted herewith for filing is the Patent Application of

Inventor: AKIRA YOSHIDA

For: WINDOW DISPLAY DEVICE and METHOD, and RECORDING MEDIUM RECORDING a WINDOW DISPLAY CONTROL PROGRAM

Enclosed with the Patent Application are:

- 5 sheet(s) of informal drawing(s)
 A Declaration and Power of Attorney
 Information Disclosure Statement (PTO Form 1449)
 A certified copy of a JAPAN application.

The filing fee has been calculated as shown below:

(Col. 1)	(Col. 2)	OTHER THAN A SMALL ENTITY
FOR:	NO. FILED	NO. EXTRA
BASIC FEE		\$ 790.00
TOTAL CLAIMS	7 - 20 = 0	x 22 = \$
INDEP. CLAIMS	6 - 3 = 3	x 82 = \$ 246.00
MULTIPLE DEPENDENT CLAIM PRESENTED		+270 = \$
*If the difference in Col. 1 is less than "0", enter "0" in Col. 2		TOTAL \$1036.00

- Please charge my Deposit Account No. 09-0460 in the amount of \$1036.00.
A duplicate copy of this sheet is attached.
- The Commissioner is hereby authorized to charge payment of the following fees
associated with this communication or credit any overpayment to Deposit
Account 09-0460. A duplicate copy of this sheet is attached.
- Any additional filing fees required under 37 CFR 1.16.
- Any patent application processing fees under 37 CFR 1.17.

EXPRESS MAIL CERTIFICATE

I hereby certify that the above paper/fee is
being deposited with the United States Postal
Service "Express Mail Post Office to Addressee"
service under 37 CFR 1.10 on the date indicated
below and is addressed to the Commissioner of
Patents and Trademarks, Washington, DC 20231.

"Express Mail" no.: E1227527621US
Date of Deposit: March 17, 1998
Person mailing paper/fee: Loretta J. Sandoval

Signature

Loretta J. Sandoval

Respectfully submitted,
AKIRA YOSHIDA

John H. Holcombe
John H. Holcombe
(#20,620)
Attorney for Applicants
Telephone 520-760-6629
IBM Corporation
Intellectual Property Law
555 Bailey Avenue J46/G463
San Jose, CA 95141

Express No. EI227527621US

WINDOW DISPLAY DEVICE AND METHOD, AND A RECORDING MEDIUM
RECORDING A WINDOW DISPLAY CONTROL PROGRAM

TECHNICAL FIELD

This invention relates to a page scrolling technique for

scrolling reduced images of page displayed in a window on a
display screen of a display device and, in particular, to a
window display device, a method of displaying a window and a
recording medium recording a window display control program for
displaying an enlarged main screen displaying a part of a page, a
sub screen displaying the entire image of that page in a reduced
form and pages preceding and following that page in a reduced
form.

BACKGROUND OF THE INVENTION

There has been proposed, in a data processing system such as

a workstation and a personal computer, an electronic filing
system (PUPA 6-168276) or an image database system (PUPA 4-28786)
for recording, saving and re-utilizing document image data.
Also, an interactive processing system (PUPA 6-259211) has been

disclosed in which a plurality of interface parts (menu and the like) for executing user interface function on the display screen of a display device are disposed in a manipulation screen panel of one window.

5 Further, among contributions to expansion of man-machine interface function of such information systems, a window display method has been provided ("DocuPlus V1.0 Operation Guide", -1-j, pp.1-5, January 29, 1997, IBM Japan) in which, in displaying image data having a page delimiter on a display screen, images of all pages are displayed in a reduced form in the window together with a main screen which displays a part of pages with enlargement, and mouse clicking on a reduced screen of a page (called thumb nail) to be moved causes the main screen to be replaced with that page. With this window display method, the user can visually confirm the page to be moved, easily select the page of the desired screen simply by mouse manipulation and immediately confirm the detail of the content in the enlarged screen so that searching information is expedited with ease.

10
15
20 In the above described window display method, however, it is necessary to adjust the display position of the main screen after the page has been switched because the area displayed in the main screen is not shown in the reduced screen in switching the screen which is to be displayed with enlargement. In addition, when the

reduced screen to be displayed with enlargement lies at the edge of the screen, adjustment of display position of the main screen has to be done at the edge of the window screen. Further, when a preceding or a next page which does not appear on the display
5 screen is to be manipulated, the user has to command scrolling each time it is manipulated.

SUMMARY OF THE INVENTION

In view of the above, it is an object of this invention to provide a window display device, a method of displaying window and a recording medium recording a window display control program which allows the page which the user wants to move to be moved to a desired area by a single manipulation.

It is another object of this invention to allow the customarily used operation on preceding/next page to be done
15 simply by manipulation of a pointing device without using a key.

To achieve the above objectives, one aspect of this invention comprises, a window display device which displays image data on a display screen a first sub-screen displaying a first area of image data, a main screen displaying a part of the first area with enlargement, a second sub-screen displaying a second area which is adjacent to the first area, a first sub-screen

image window for displaying an area displayed in the main screen
with a display indicating frame on the first sub-screen, a main
screen image window for moving the display indicating frame and
the display area within the main screen in correspondence to an
5 output representing movement of a pointing device as notified by
the first sub-screen window, the first sub-screen window causing
the display indicating frame to be moved within the first sub-
screen while the pointing device is in dragging state and, a
second sub-screen image window for displaying the display
indicating frame in the second sub-screen when the pointing
device has moved the display indicating frame by dragging it into
the second sub-screen.

Another aspect of this invention comprises, a window display
device which displays image data having a page delimiter on a
display screen a main screen displaying a part of a page with
enlargement, a first sub-screen displaying the image of that page
in a sub-screen column, a second sub-screen displaying one or
more second areas which is adjacent to the page, a first sub-
screen image window for displaying a reduced image of a page
20 which is currently displayed on the main screen with the area
displayed in the main screen indicated by a display indicating
frame, a main screen image window for moving the display
indicating frame and the display area within the main screen in

correspondence to an output representing movement of a pointing device as notified by the first sub-screen window, the first sub-screen window causing the display indicating frame to be moved within the same page while the pointing device is in dragging state, a second sub-screen image window for displaying the display indicating frame in the second sub-screen when the pointing device has moved the display indicating frame by dragging it into the second sub-screen, a display screen parent window operative when the pointing device has dropped the display indicating frame at an arbitrary place on the second screen to which the pointing device moved, for switching the main screen to the page to which the pointing device moved and displaying the place indicated by the display indicating frame in the main screen and a sub-screen parent window for scrolling the sub-screen so that the sub-screen of the page displayed on the main screen comes to a predetermined position of the sub-screen column.

In the above, the sub-screen parent window scrolls the sub-screen so that the sub-screen of the page displayed on the main screen comes to substantially the central position of the sub-screen column.

Another aspect of this invention comprises a window display method of displaying image data on a display screen of a display

device having a first sub-screen displaying a first area of image data, a main screen displaying a part of the first area with enlargement and a second sub-screen displaying a second area which is adjacent to the first area, the method comprising the steps of; displaying an area displayed in the main screen with a display indicating frame on the first sub-screen, moving the display indicating frame and the display area within the main screen in correspondence to the movement of a pointing device which causes the display indicating frame to be moved within the first sub-screen while the pointing device is in dragging state and, displaying the display indicating frame in the second sub-screen when the pointing device has moved the display indicating frame by dragging it into the second sub-screen.

Another aspect of this invention comprises a window display method of displaying image data having a page delimiter on a display screen of a display device having a main screen displaying a part of a page with enlargement, a first sub-screen displaying the image of that page and a second sub-screen displaying one or more second areas which is adjacent to the page, the method comprising the steps of; displaying a reduced image of a page which is currently displayed on the main screen with the area displayed in the main screen indicated by a display indicating frame, moving the display indicating frame and the

display area within the main screen in correspondence to the movement of a pointing device which causes the display indicating frame to be moved within the same page while the pointing device is in dragging state, displaying the display indicating frame in the second sub-screen when the pointing device has moved the display indicating frame by dragging it into the second sub-screen, switching the main screen to the page to which the pointing device moved to display the place indicated by the display indicating frame in the main screen when the pointing device has dropped the display indicating frame at an arbitrary place on the second screen to which the pointing device moved to display the place indicated by the display indicating frame in the main screen, and scrolling the sub-screen so that the sub-screen of the page displayed on the main screen comes to a predetermined position of the sub-screen column.

Another aspect of this invention relates to a recording medium recording a display control program for displaying image data on a display screen of a display device, the display control program causing a computer to: display a first sub-screen displaying a first area of image data, display a main screen displaying a part of the first area with enlargement, display a second sub-screen displaying a second area which is adjacent to the first area display the area displayed in the main screen on

the first sub-screen with a display indicating frame, move the display indicating frame and the display area within the main screen in correspondence to the movement of a pointing device which causes the display indicating frame to be moved within the
5 first sub-screen while the pointing device is in dragging state and, display the display indicating frame in the second sub-screen when the pointing device has moved the display indicating frame by dragging it into the second sub-screen.

Another aspect of this invention relates to a recording medium recording a display control program for displaying image data having a page delimiter on a display screen of a display device, the display control program causing a computer to:
10 including a main screen displaying a part of a page with enlargement, a first sub-screen displaying the image of that page and a second sub-screen displaying one or more second areas which is adjacent to the page display a reduced image of a page which is currently displayed on the main screen with the area displayed in the main screen indicated by a display indicating frame, move the display indicating frame and the display area within the main screen in correspondence to the movement of a pointing device
15 which causes the display indicating frame to be moved within the same page while the pointing device is in dragging state,
20 display the display indicating frame in the second sub-screen

when the pointing device has moved the display indicating frame by dragging it into the second sub-screen, switching the main screen to the page to which the pointing device moved to display the place indicated by the display indicating frame in the main screen, when the pointing device has dropped the display indicating frame at an arbitrary place on the second screen to which the pointing device moved and, scroll the sub-screen so that the sub-screen of the page displayed on the main screen comes to a predetermined position of the sub-screen column.

For a fuller understanding of the present invention, reference should be made to the following detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of a hardware configuration of a data processing system to which this invention is preferably applied.

Fig. 2 is a plan view of a detailed example of the display screen implementing the visual page scrolling function of this invention.

Fig. 3 is a schematic diagram showing the steps of operation of this invention.

Fig. 4 is a block diagram showing a program structure of the window implementing the visual page scrolling function of this
5 invention.

Fig. 5 is a flow chart showing an example of control operation of the window of Fig. 4.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the invention will now be described with reference to the drawings herewith.

Hardware Embodiment

Fig. 1 shows an example of a hardware configuration of a data processing system to which this invention is preferably applied. The data processing system 100 may be implemented by a conventional workstation and a personal computer and comprises a main CPU (central processing unit) 1 such as a microprocessor which controls arithmetic operation of the entire system and a

main memory **4** which is used for working area of the CPU. The CPU
1 and the main memory **4** are connected to other components
including a hard disk device **13** as an auxiliary storage, a ROM **14**
for storing a constant, a serial port **15** for a modem, a parallel
5 port **16** for a printer, a timer **17** and a communication adapter **18**
through a bus **2**.

A floppy disk device **20** which drives a floppy disk such as
MO and CD-ROM is connected to the bus **2** through a floppy disk
controller **19**. A computer program code as shown in Fig.5 which
gives instructions to the CPU and the like in cooperation with an
operating system to practice this invention is recorded in the
floppy disk, the hard disk device **13** and the ROM **14** and executed
by being loaded in the memory **4**.

Further, as a user interface hardware, there are a pointing
device **7** such as a mouse and a joystick, a keyboard **6** and a
display (image display device) **12** as shown in Fig. 2 for
displaying an image. The mouse **7** and the keyboard **6** are
connected to the bus **2** via a keyboard mouse controller **5**. A
display device **11** such as the display **12** and a display lump are
20 connected to the bus **2** via a display drive control device **10**
having a digital-analog converter and a video graphic array **8** to
which is also connected a video RAM **9**. A speaker **23** receives an

audio signal which is digital-analog converted by an audio controller **21** via an amplifier **22** for output as a voice. The audio information from a microphone **24** is taken in the system after it is analog-digital converted by the audio controller **21**.

5 It should be understood that these components are shown as an example and all of them are not necessarily indispensable components of this invention. For instance, the microphone **24** may be removed and instead an image reading device or a character recognition device may be connected if needed.

10 While an operating system which supports as a standard a GUI (graphic user interface) multi-window environment such as Windows (trademark of Microsoft), OS/2 (trademark of IBM) and X-WINDOW system (trademark of MIT) on AIX (trademark of IBM) is preferable, those supporting a character base environment such as PC-DOS (trademark of IBM) and MS-DOS (trademark of Microsoft) may be workable because the GUI environment may be provided in the application side and the operating system is not limited to any specific operating system environment.

Embodiment of Display Screen

20 Fig. **2** shows a detailed example of a display screen implementing a visual page scrolling function of this invention.

In this figure, **50** is a main screen (main window screen) displaying a part of a page with enlargement in displaying image data which has a page delimiter in the display **12** in Fig. 1. **51** is a sub-screen (page view sub-window screen) displaying the image of the entire page which is currently displayed on the main screen **50**. **52** is a sub-screen displaying the page preceding to the page currently displayed on the main screen **50** while **53** is a sub-screen displaying the page next to the page currently displayed on the main screen **50**.

These sub-screens **52**, **51**, **53** are so laid out that they are disposed vertically in sequence at the right edge of the display screen with the sub-screen **51** of the page displayed on the main screen **50** being at the center of the sequence. In other word, in page movement, the sub-screen is scrolled so that the reduced screen of the moved page comes to the display position of **51**.

While one preceding page and one next pages of the central sub-screen **51** are displayed in the example shown in Fig. 2, more pages may be displayed. For example, when the display area of the main screen **50** is relatively small, all pages (e.g., more than 10 pages) may be displayed at one time. Further, when the image continues horizontally and vertically as in the case of a map, a two dimensional array is possible.

The area currently displayed in the main screen **50** is displayed with a rectangle (hereinafter called a view frame) **60** on the sub-screen **51** of the page which is displayed on the main screen **50** in order to indicate in which part of the entire page it is. The rectangle of the view frame **60** is either uniformly painted with a predetermined light color or displayed in inverted color so as to make the extent of display of the current main screen immediately recognizable on the sub-screen **51**.

Incidentally, this view frame **60** may be called either one of a display indicating frame, a document display area, an inverted area and a display position rectangle.

Examples of various tool bar buttons **31 - 46** are displayed in the upper part of the main screen **50**. Depression of a page designating button **34** in the tool bar causes a jump to the designated page, depression of a start page button **35** causes the first page to be displayed, depression of a last page button **36** causes the last page to be displayed, depression of a preceding page button causes the preceding page to be displayed and depression of a next page button causes the next page to be displayed.

With respect to the main screen **50**, depression of counterclockwise rotation button **39** in the tool bar causes the

JA997028

display screen to be rotated counterclockwise, depression of clockwise rotation button **40** causes the display screen to be rotated clockwise, depression of maximize button **41** causes the screen displayed to be maximized, depression of minimize button **42** causes the screen displayed to be minimized, depression of enlarge button **43** causes the screen displayed to be enlarged and depression of reduce button **44** causes the screen displayed to be reduced.

The sub-screen **51 - 53** may be selectively displayed or not displayed as required. By selecting window view in the menu or depressing the page view button **45** in the tool bar, display/non display is alternated. In addition, the number of sub-screens of display (e.g., 7 at maximum) may be variably set.

In addition, there are a help button **46** displaying a help screen, a print button **31** for printing a ledger, a check stamp menu button **32** displaying check stamp menu and, a search button **33** for searching through the ledger. Further, information relating to the display of the main screen **50** is displayed in letters above the buttons **31 - 46** of the tool bar. However, these buttons and messages are for exemplary purpose and all of them are not necessarily indispensable components. A screen structure of different layout may be used.

Mode of Operation

Next, an example of operation of this invention is now described with reference to Fig. 3. Incidentally, this figure is schematically depicted by eliminating various buttons and document displays of Fig. 2 to simplify the illustration.

As shown in Fig. 3(A), the area displayed in the main screen is displayed by a rectangular view frame 60 on the sub-screen 51 of the page (page 12 in this figure) currently displayed on the main screen 50. The view frame 60 is shown, for example, as an inverted area by inverted display. By dragging the view frame (with the left button of the mouse held depressed within the view frame 60) in the central sub-screen 51 through the same page, the display area in the main screen 50 also moves in real time.

Next, by dragging the view frame 60 to the neighboring page, e.g., the preceding page (page 11 in this figure), the view frame 60 moves into the sub-screen 52 to which the view frame 60 moved.

By dropping (releasing the left button of the mouse) at a place on the sub-screen 51 to which the view frame is dragged and where it is desired to display, the main screen 50 switches to that page (page 11) at the timing of dropping as shown in Fig. 3(C) to display the place indicated by the rectangular view frame

60 in the main screen 50. Simultaneously, the sub-screen is scrolled so that the sub-screen of the page displayed in the main screen 50 comes to the center of the sub-screen column.

By repeating the above operation, consecutive preceding 5 pages (or following pages) are displayed one after another on the main screen and thus the sub-screen is scrolled so that this provides the visual page scrolling function in lieu of the next page/preceding page key or the next page/preceding page button 37, 38.

While movement to the preceding page is shown in Fig. 3, the same visual page scrolling as the above described one is performed by the same operation as the above for movement to the next page.

Display Control Method

Fig. 4 shows a program structure of the window for implementing the visual page scrolling function of this invention described in Fig. 3 and the flow chart of Fig. 5 shows an example of the control procedure therefor.

The window implementing this invention (window procedure) comprises n sub-screen image windows 201 corresponding to the number of sub-screens n, sub-screen parent window 210, main

screen image window **220** and display screen parent window **230** as shown in Fig. 4 and information is exchanged as shown by the arrow heads in Fig. 4.

The sub-screen image window **201** provides movement and re-drawing of the view frame **60** according to dragging and dropping of the mouse and the movement of the mouse. The sub-screen parent window **210** provides creation and movement (scroll) of the sub-screen image window **201** corresponding to the moved page which is notified from the sub-screen image window **201**.

The main screen image window **220** provides; movement of the display screen position of the main screen **50** corresponding to the movement of the mouse which is notified from the sub-screen image window **201**, drawing of the page designated corresponding to the moved page which is notified from the sub-screen image window **201** and, movement of the display screen position of the main screen **50** corresponding to the display position information which is then notified from the sub-screen image window **201**.

Next, the control operation in the embodiment of this invention is now described in detail with reference to the flow chart of Fig. 5. In the figure, **S** represents a step.

First of all, when the sub-screen image window **201** of the sub-screen **51** of the page currently displayed on the main screen

JA997028

50 detects that the view frame 60 (inverted area) has been dragged by the mouse (S1), acquisition of WM-MOUSEMOVE message (signal) of the mouse 7, that is so called mouse capture is started (S2).

5 When the sub-screen image window 201 detects that the view frame 60 has moved within the sub-screen 51 (S3) based on the output of the mouse (WM-MOUSEMOVE), it causes the view frame 60 on the sub-screen 51 to move corresponding to the movement of the mouse and notifies the movement to the main screen image window 220 (S4). When the view frame 60 is dropped, the process is terminated as it is while the process returns to the determination at S3 when it is not dropped (S5).

10 The main screen image window 220 provides movement of display screen position of the main screen 50 corresponding to the movement of the mouse which is notified from the sub-screen image window 201 (S6). Thus, by dragging the view frame 60 in the central sub-screen 51 within the same page, the display area within the main screen also moves in real time.

15 On the other hand, when the sub-screen image window 201 determines based on the output of the mouse that it moves out of the sub-screen 51 into the sub-screen of another page (S3), it re-draws an inverted rectangle of the view frame 60 in the moved

sub-screen (**S7**). The sub-screen image window **201** then determines whether or not the mouse is dropped (**S8**) and the process returns to the determination step **S3** if not dropped while the moved page is notified to the sub-screen parent window **210** and the main screen image window **220** substantially simultaneously (**S9**) if dropped.

When the sub-screen parent window **210** is notified of the moved page from the sub-screen image window **201**, it provides creation and movement (scroll) of the sub-screen image window **201** so that the sub-screen of the designated page is displayed at the center.

10
15
20

20

When the main screen image window **220** receives a notification of the moved page from the sub-screen image window **201**, it provides a reference drawing of the designated page for the main screen **50** (**S11**) and notifies sub-screen image window **201** of completion of drawing when drawing is completed (**S12**). When the sub-screen image window **201** receives the notification of completion of drawing, it notifies the main screen image window **220** of the display position information of the view frame **60** (**S13**). When the main screen image window receives the notification of the display position information, it moves the

display screen position of the main screen 50 corresponding to the notified display position information (**S14**).

Because the sub-screen image window 201 is processed in parallel with the main screen image window 220, dragging the view frame to a neighboring page causes the main screen 50 to be switched to that page at the time the view frame is dropped and the place indicated by the view frame 60 is displayed in the main screen while the sub-screen is scrolled so that the sub-screen of the page displayed in the main screen comes to the center of the sub-screen column.

Although omitted in the flow chart of Fig. 5, when the page designation button 34 of Fig. 2 is depressed in the tool bar, the page jumps to the designated page which is displayed in the main screen 50 and the sub-screen 51 of that page is displayed in the center of the sub-screen column. However, when the page jumps to the first page by the page designation button 34 or the start page button 35 of Fig. 2 is depressed, the sub-screen 52 of the first page is displayed on top of the sub-screen column in displaying the first page in the main screen 50. Similarly, when the page jumps to the last page or the last page button 36 of Fig. 2 is depressed, the sub-screen 53 of the last page is

displayed at the tail of the sub-screen column in displaying the last page in the main screen 50.

While a mouse was shown as an input means in the above embodiment of this invention, the input means may include other 5 pointing devices (coordinate indicator) such as a track pad, a track ball, a digitized, a tablet and a joystick without being limited to a mouse.

While display of image data having a page delimiter was shown in the above embodiment, this invention is not limited to such image data. By providing a sub-screen into which a part of entire drawing is reduced, a simple movement to a place to which movement is desired is also possible for image data such as a map which is not delimited by page.

Further, the embodiment of this invention includes a recording medium which stored therein a control program represented by a software implementing this invention.

Effect of Invention

As described in the above, the following effects are obtained according to this invention.

5

(1) The user can move to an area where it is desired to display in the page to which it is desired to move at one manipulation because the user can instantly see which place is displayed with enlargement when switching screens by seeing the movement display of the view frame (display indication frame).

(2) Because the sub-screen is scrolled so that the sub-screen of the switched screen is displayed substantially at the center of the sub-screen column in switching screens, next page/preceding page operation which is frequently used in practice can be simply done only by manipulating a pointing device without using a key. Therefore, movement of user's eye and hand is minimized thereby contributing to faster and easier operation as well as user friendliness.

16

15 an entire page is reduced and scrolling the sub-screen so that
the sub-screen of the switched screen is displayed substantially
in the center of the sub-screen column in switching screens, the
user can easily and quickly confirm visually the page which it is
desired to move for moving the page.

20 While the preferred embodiments of the present invention
have been illustrated in detail, it should be apparent that

JA997028

modifications and adaptations to those embodiments may occur to one skilled in the art without departing from the scope of the present invention as set forth in the following claims.

Description of Reference Numbers

- 5 **1:** Main CPU
2: Bus
4: Main Memory
5: Keyboard Mouse Controller
7: Mouse
10 **12:** Display
14: ROM
50: Main Screen
51, 52, 53: Sub-screen
60: View Frame (display indicating frame)
15 **201:** Sub-screen Image Window
210: Sub-screen Parent Window
220: Main Screen Image Window
230: Display Screen Parent Window

I claim:

1 1. A window display device which displays image data on a
2 display screen, comprising:
3 a first sub-screen displaying a first area of image data;
4 a main screen displaying a part of said first area with
5 enlargement;
6 a second sub-screen displaying a second area which is
7 adjacent to said first area;
8 a first sub-screen image window for displaying an area
9 displayed in said main screen with a display indicating frame on
10 said first sub-screen;
11 a main screen image window for moving said display
12 indicating frame and said display area within said main screen in
13 correspondence to an output representing movement of a pointing
14 device as notified by said first sub-screen window, said first
15 sub-screen window causing said display indicating frame to be
16 moved within said first sub-screen while said pointing device is
17 in dragging state; and
18 a second sub-screen image window for displaying said display
19 indicating frame in said second sub-screen when said pointing
20 device has moved said display indicating frame by dragging it
21 into said second sub-screen.

1 2. A window display device which displays image data having a
2 page delimiter on a display screen, comprising:

3 a first sub-screen displaying a first area of image data in
4 a sub-screen column;

5 a main screen displaying a part of said first area with
6 enlargement;

7 a second sub-screen displaying in said sub-screen column a
8 second area which is adjacent to said first area;

9 a first sub-screen image window for displaying a reduced
10 image of a page which is currently displayed on said main screen
11 with said area displayed in said main screen indicated by a
12 display indicating frame;

13 a main screen image window for moving said display
14 indicating frame and said display area within said main screen in
15 correspondence to an output representing movement of a pointing
16 device as notified by said first sub-screen window, said first
17 sub-screen window causing said display indicating frame to be
18 moved within the same page while said pointing device is in
19 dragging state;

20 a second sub-screen image window for displaying said display
21 indicating frame in said second sub-screen when said pointing
22 device has moved said display indicating frame by dragging it
23 into said second sub-screen;

24 a display screen parent window operative when said pointing
25 device has dropped said display indicating frame at an arbitrary
26 place on said second screen to which said pointing device moved,
27 for switching said main screen to the page to which said pointing
28 device moved and displaying the place indicated by said display
29 indicating frame in said main screen; and

30 a sub-screen parent window for scrolling said sub-screen so
31 that the sub-screen of the page displayed on said main screen
32 comes to a predetermined position of said sub-screen column.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32

3. The window display device of Claim 2 in which said sub-
screen parent window scrolls said sub-screen so that the sub-
screen of the page displayed on said main screen comes to
substantially the central position of said sub-screen column.

1 4. A window display method of displaying image data on a
2 display screen of a display device having a first sub-screen
3 displaying a first area of image data, a main screen displaying a
4 part of said first area with enlargement and a second sub-screen
5 displaying a second area which is adjacent to said first area,
6 said window display method comprising the steps of:

7 displaying an area displayed in said main screen with a
8 display indicating frame on said first sub-screen;

9 moving said display indicating frame and the display area
10 within said main screen in correspondence to the movement of a
11 pointing device which causes said display indicating frame to be
12 moved within said first sub-screen while said pointing device is
13 in dragging state; and

14 displaying said display indicating frame in said second sub-
15 screen when said pointing device has moved said display
16 indicating frame by dragging it into said second sub-screen.

1 5. A window display method of displaying image data having a
2 page delimiter on a display screen of a display device having a
3 main screen displaying a part of a page with enlargement, a first
4 sub-screen displaying the image of that page in a sub-screen
5 column and a second sub-screen displaying one or more second
6 areas which is adjacent to said page, said window display method
7 comprising the steps of:

8 displaying a reduced image of a page which is currently
9 displayed on said main screen with the area displayed in said
10 main screen indicated by a display indicating frame;

11 moving said display indicating frame and said display area
12 within said main screen in correspondence to the movement of a
13 pointing device which causes said display indicating frame to be
14 moved within the same page while said pointing device is in
15 dragging state;

16 displaying said display indicating frame in said second sub-
17 screen when said pointing device has moved said display
18 indicating frame by dragging it into said second sub-screen;

19 switching said main screen to the page to which said
20 pointing device moved to display the place indicated by said
21 display indicating frame in said main screen when said pointing
22 device has dropped said display indicating frame at an arbitrary
23 place on said second screen to which the pointing device moved to

JA997028

24 display the place indicated by said display indicating frame in
25 said main screen; and
26 scrolling said sub-screen so that the sub-screen of the page
27 displayed on said main screen comes to a predetermined position
28 of said sub-screen column.

1 6. A recording medium recording a display control program for
2 operating a computer system having a display device for
3 displaying image data on a display screen of said display device,
4 said display control program causing said computer system to:
5 display a first sub-screen displaying a first area of image
6 data;
7 display a main screen displaying a part of said first area
8 with enlargement;
9 display a second sub-screen displaying a second area which
10 is adjacent to said first area;
11 display the area displayed in said main screen on said first
12 sub-screen with a display indicating frame;
13 move said display indicating frame and said display area
14 within said main screen in correspondence to the movement of a
15 pointing device which causes said display indicating frame to be
16 moved within said first sub-screen while said pointing device is
17 in dragging state; and
18 display said display indicating frame in said second sub-
19 screen when said pointing device has moved said display
20 indicating frame by dragging it into said second sub-screen.

1 7. A recording medium recording a display control program for
2 operating a computer system having a display device for image
3 data having a page delimiter on a display screen of a display
4 device, said display control program causing said computer system
5 to:

6 display a main screen displaying a part of a page with
7 enlargement:

8 display first sub-screen displaying the image of that page
9 in a sub-screen column;

10 display a second sub-screen displaying one or more second
11 areas which is adjacent to said page in said sub-screen column;

12 display a reduced image of a page which is currently
13 displayed on said main screen with the area displayed in said
14 main screen indicated by a display indicating frame;

15 move said display indicating frame and said display area
16 within said main screen in correspondence to the movement of a
17 pointing device which causes said display indicating frame to be
18 moved within the same page while said pointing device is in
19 dragging state;

20 display said display indicating frame in said second sub-
21 screen when said pointing device has moved said display
22 indicating frame by dragging it into said second sub-screen;

JA997028

23 switching said main screen to the page to which said
24 pointing device moved to display the place indicated by said
25 display indicating frame in said main screen, when said pointing
26 device has dropped said display indicating frame at an arbitrary
27 place on said second screen to which said pointing device moved;
28 and

29 scroll said sub-screen so that the sub-screen of the page
30 displayed on said main screen comes to a predetermined position
31 of said sub-screen column.

WINDOW DISPLAY DEVICE AND METHOD, AND A RECORDING MEDIUM


RECORDING A WINDOW DISPLAY CONTROL PROGRAM

ABSTRACT


The disclosed invention allows the user to move to an area
5 to which the user desires to display in a page to which the user
desires to move by a single manipulation and to allow next
page/preceding page operation to be done only by a mouse
operation. An area displayed on the main screen 50 is displayed
on the sub-screen 51 of a reduced image of the page which is
10 currently displayed on the main screen 50 with a rectangular view
frame 60. Dragging the view frame 60 by a mouse within the page
causes the display area in the main screen to move in real time.
Dragging the view frame of the sub-screen 51 to a neighboring
page causes the view frame 60 to be moved in the moved sub-
screen. Dropping the view frame at the place on the neighboring
15 sub-screen to which the view frame 60 moved causes the main
screen to be switched to that page to display the place indicated
by the view frame in the main screen. Simultaneously, the sub-
screen is scrolled so that the sub-screen of the page displayed
20 in the main screen comes to the center of the sub-screen column.

[Document Type] Drawing

[Figure 1]




[Figure 2]




[Figure 3]


(A)




(B)




(C)



[Figure 4]



[Figure 5]



DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION
DOCKET: JA997028

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

WINDOW DISPLAY DEVICE and METHOD, and RECORDING MEDIUM RECORDING a WINDOW DISPLAY CONTROL PROGRAM

the specification of which (check one)

is attached hereto.

was filed on _____
as Application Serial No. _____

and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s) Priority Claimed

09-68537 JAPAN 21/03/97 Yes No
(Number) (Country) (Day/Month/Year Filed)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56, which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

None (Application Serial No.) (Filing Date) (Status) (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

DOCKET: JA997028

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

David J. Kappos (#34,357)
Prentiss W. Johnson (#22,123)
Christopher A. Hughes (#26,914)
John H. Hoel (#26,)
Ingrid M. Foerster (#36,511)

Marilyn Smith Dawkins (#31,140)
John H. Holcombe (#20,620)
Edward A. Pennington (#32,588)
Joseph C. Redmond (#32,588)

Send correspondence to: D. A. Kappos
IBM Corporation
Intellectual Property Law
555 Bailey Avenue
San Jose CA 95141

Direct Telephone Calls to: (name and telephone number) John H. Holcombe, 520-760-6629

Full name of sole or first joint-inventor: AKIRA YOSHIDA

YOSHIDA

Inventor's signature: Date:

Residence: #304, 2-15-10 Shibuya, Yamato-shi, Kanagawa-ken, JAPAN

Citizenship: Japan

Post Office Address: Same

YOSHIDA